

Certificate of Product Approval

Certificate Number: 1097e

Issue: 01

Premier Security Solutions Limited

Unit 2
19-21 Roebuck Road
Hainault Business Park
Hainault
Essex
IG6 3TU

is authorised to use the LPCB mark in association with the product(s) listed in this certificate and appendix having complied with the requirements of the standard(s) detailed below:

Products

SBD G-81
security gates

Standard

LPS 2081: Issue 1

Requirements and testing procedures for the LPCB approval and listing of building components, strongpoints, security enclosures and free-standing barriers offering resistance to intruders attempting to use stealth to gain entry

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for LPCB

Paul Dillon
Verifier

11 September 2018
Date of Issue

11 September 2018
Date of First Issue



This certificate and appendix remain the property of BRE Global Ltd and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

LPCB is part of BRE Global Ltd, Garston, Watford, WD25 9XX
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: enquiries@breglobal.com



Appendix to Certificate No: 1097e Premier Security Solutions Limited

Issue: 01

Security Gates

Product Name	Type	Minimum Structural Opening Height (m)	Maximum Structural Opening Height (m)	Minimum Structural Opening Width (m)	Maximum Structural Opening Width (m)	Compatible Locking Systems	Security Rating	LPCB Ref. No.
SBD G-81	Single leaf outward opening gate	0.579	3.139	0.526	1.926	1 to 5	B	1097e/01
	Single leaf outward opening gate with side and/or over panels ¹	0.579	6.0	0.526	Unlimited	1 to 5	B	
	Single leaf inward opening gate	0.579	3.139	0.526	1.926	1 to 5	B	
	Single leaf inward opening gate with side and/or over panels ¹	0.579	6.0	0.526	Unlimited	1 to 5	B	

Compatible Locking Systems²

Locking System	Locking System				Operating Devices		Compatible Cylinders
	Manufacturer	Model	Type	Quantity	External Face	Internal Face	
1	Securitron	M32	Maglock	Two	Access control system ³	Push button release ⁴ or access control system ³	None
2	Securitron	M32	Maglock	Three	Access control system ³	Push button release ⁴ or access control system ³	None
3	Securitron	M62	Maglock	Two	Access control system ³	Push button release ⁴ or access control system ³	None
4	IGEM	5000	Maglock	Two	Access control system ³	Push button release ⁴ or access control system ³	None
5	IGEM	5000	Maglock	Three	Access control system ³	Push button release ⁴ or access control system ³	None

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for LPCB

Paul Dillon
Verifier

11 September 2018
Date of Issue

11 September 2018
Date of First Issue



This certificate and appendix remain the property of BRE Global Ltd and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR Tag or contact us.

LPCB is part of BRE Global Ltd., Garston, Watford WD25 9XX.

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: Enquiries@breglobal.com




Appendix to Certificate No: 1097e Premier Security Solutions Limited

Issue: 01

Compatible Design Features / Accessories⁵

Design Feature / Accessory	Product Name
	SBD G-81
Continuous stainless steel 'anti-nip' piano hinge	✓
EIS 7800q access control entry panel ³	✓
Urmet 2Voice, S-Steel, V-Steel, Transit, Passan or RTE14 access control entry panel ³	✓
Vertical barset infill	✓

Notes:

1. The sizes of gate approved in this configuration fall within the size ranges for the single leaf gates, i.e. those without a side and/or overhead panel.
2. Certification does not cover the use of locks other than those listed in the table. Utilisation of unlisted locks may affect the level of security offered by the gate.
3. The access control system's resistance to "non-mechanical" attack has not been assessed as it is outside the scope of LPS 2081. It is therefore recommended that specifiers satisfy themselves that the components used are resistant to any environmental conditions/interference that may cause the locking system to disengage. Furthermore, specifiers should ensure the access control system incorporates provision for uninterrupted power to be provided to the electromagnetic locks in the event of a mains power failure, if the gate is required to continue to provide the certified resistance to forced entry during such an event, and that appropriate means of escape is assured in an emergency.
4. The access control systems' 'push to release' button must be located at least 1.5 m from the gate and any associated side and/or over panels.
5. For details of the sizes and configuration details of the infill panels and options please refer to the manufacturer. The scope of approval covers the use of different infill types within the gate and side and/or over panels.

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for LPCB

Paul Dillon
Verifier

11 September 2018
Date of Issue

11 September 2018
Date of First Issue



This certificate and appendix remain the property of BRE Global Ltd and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR Tag or contact us.

LPCB is part of BRE Global Ltd., Garston, Watford WD25 9XX.
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: Enquiries@breglobal.com


